

Specification - Pecol Solar Hot Water System



Total Capacity	66 Gal Or 300 L
Overall Length	2439mm
Overall Width	2286mm
Overall Height	508mm
Outer Tank Diameter	508mm
Outer Tank Length	2296mm
Nominal Working Pressure	500kPa
Cylinder Test Pressure	1500kPa
Relief Valve Settings	700kPa
Weight Empty (Total)	128kg
Weight Full (Total)	432kg
Outer Cylinder Case Material	Zincalume
Tank Insulation	Polyurethane
Thermostat	Sunvic

TANK INSULATION	
A) Insulation Material	Polyurethane
B) Method	High Pressure Injection
C) Weight	10kg (approx)

SOFT FLOW WATER SPREADER	
A) Diameter	30mm
B) Length	1.6m
C) Material Specification	Stainless Steel

TANK	
A) Cylinder Body Length	2133mm
B) Cylinder Body End	64mm
C) Cylinder Diameter	410mm
D) Cylinder Material	1.5mm ss 304

COLLECTOR CASING	
A) Material	Zincalume
B) Thickness	0.45mm
C) Vent Holes	2
D) Trim Depth	15mm

LOW IRON CLEAR TEMPERED GLASS	
A) Thickness	4mm
B) Size	994mm x 1918mm
C) Insulation Material	Rockwool

COLLECTOR	
A) Length	1930mm
B) Width	1003mm
C) Height	51mm
D) Absorber Plate Design	Tube & Fin
E) Absorber Plate Material	Aluminium
F) Absorber Plate Thickness	1.2mm
G) Nett Absorber Area (Single)	2sq.m
H) Absorber Plate Coating	Ultra Black Chromatic
I) Absorber Coefficient	0.95
J) Emission Coefficient	0.1
K) Coefficient Tolerance	+/-0.02
L) No. of Riser Tubes	6
M) Riser Tube Material Thickness	0.71
N) Riser Bond	Thermal Bond
O) Riser Plate Spacing	139mm
P) Riser Joint Type	Brazed
Q) Panel to Panel Joint	22mm Compression Fitting
R) Leak Test Pressure	800kPa
S) Over Pressure Test	1500kPa

OVERALL DIMENSIONS	
A) Overall Tank Length	2286mm
B) Overall Length of System	2438mm
C) Tank Height	508mm
D) Collector Length	1930mm
E) End Cap Width	41mm
F) Collector Width (Single)	1003mm
G) Collector Width (Complete)	2199mm
H) Tank Width	508mm
I) Tank Height	508mm
J) Overall Length of System	2286mm
K) Collector Height	51mm

END CAP	
A) End Cap Seal Material	EPDM Blend UV Protected
B) End Cap Seal Width	13mm
C) End Cap Material	0.9mm Powder Coated Steel
D) End Cap Width	41mm
F) End Cap Diameter	508mm

Solar Hot Water System





PECOL ENGINEERING SDN BHD (1189842-M)
PACIFIC ENGINEERING SDN BHD (8073-K)

HQ: Lot 30, Jalan 223, Section 51-A 46100 Petaling Jaya, Selangor, Malaysia.
Tel: +603-7957 2588 Fax: +603-7958 7081
Email: pecol@pecol.com.my Website: www.pecol.com.my

Branch: Blk D-9-6, Level 11, Menara Uncang Emas, 85, Jalan Loke Yew, 55200 Kuala Lumpur. Tel: 03 9200 3588 Fax: 03 9200 3589

Email: sales@pecol.com.my / pecol@pecol.com.my
Contact Number: 012-323 6388 / 012-387 9188 / 012-387 1876

Authorised Dealer

We're Here Today To Help You Save For Tomorrow

Pecol Solar Hot Water System is a proven system that has been manufactured and developed over the years by Pacific Engineering Sdn Bhd. Our latest solar hot water system is the result of extensive research and development which incorporates the most advanced technology from USA. The PECOL design team had created this modern, durable and high efficiency system that will blend beautifully with most housing styles to meet your hot water heating needs.

Environmentally friendly,
reduces your carbon footprint.



- Free hot water from the sun.
- Enhanced energy retention.
- Ultra fast heating.
- Built to last.
- Meets international quality and safety standard.
- Reliable in house before and after sales services.
- Reliable and efficient.
- Air tight seal design.
- Pollution free.
- Manufacturer warranty.



Solar Hot Water System

- 1 Ultra Solid Frame**
Premium grade material are used throughout the construction of every Pecol Solar Hot Water System.
- 2 Ultra Fast Heating**
Pecol solar water system has been precisely engineered to meet the need for constant hot water. It trap solar energy at a faster rate with its larger surface of area to allows better heat absorption.
- 3 Extra Energy Saving**
Pecol crystal clear low iron tempered glass specially designed to allow the ultimate transmission of sunlight with negligible emission of heat directly onto the ultra black chromatic collector. The near 'Perfect Bank' UBC collector has an extra absorption power to deliver higher performance compared to any other collector.
- 4 Best Insulation**
Pecol uses pressure injected high density polyurethane foam to restrict minimal heat lost to the atmosphere surrounding even at tremendous temperature difference.
- 5 Built to Last**
Quality workmanship and quality material are pecol commitment. We assure high durability to give great value to your investment.
- 6 Hot Water All Year Round**
Pecol comes with built in electrical backup for heating element for additional hot water needed during monsoon season efficiently maintain desired temperature anytime during rainy days.
- 7 Prolong Hot Water Temperature**
Pecol has incorporated soft-flow water spreader to prevent make-up cold water from mixing freely with the heated water.
- 8 Pressure Solar Tank**
Pecol's optimum water flow is designed to enable the right flow of hot water throughout your entire hot water plumbing system.
- 9 Tougher Protection**
Pecols uses an UV treated air-light seal all around the side and goes all round the solar hot water tank to prevent rain water and other corrosive particles in the air seeping through.
- 10 State-Of-The-Art Design**
The trendy and stylish slim like design is designed to blend into harmony of any roof profile.
- 11 Maintenance Free**
Pecols has perfected the welds by using high technology robotic welding also to compressed seal by the quality brass fittings are used form preffered system.
- 12 Warranty**
Pecols provide 10 years warranty after purchased.